



INDUSTRIAL DIESEL GENERATOR



Specifications

ENGINE	
Manufacturer	Kohler
Engine Model	KDI1903M
EPA Certification	Tier 4 Final
Rated	1800 RPM
Nominal Power (PRIME)	18.75KVA / 15KW
Nominal Power (STANDBY)	20.63KVA / 16.5KW
Engine Type	Diesel 4 Stroke
Injection Type	Direct Injection
Cylinders / FIE	3 / Mechanical Rotary Pump
Bore	88mm
Stroke	102mm
Displacement	1.9L
Cooling System	Liquid Cooled
Valves Per Cylinder	4
COOLING SYSTEM	
Radiator Coolant Capacity	6.5L
Fan Type	350mm Pusher
EXHAUST SYSTEM	
Emissions Management	No Aftertreatment
LUBRICATION SYSTEM	
Oil Filter Type	Spin On
Oil Capacity	8.5L
Oil Consumption @ Full Load	<0.1%
Recommended Oil	5W-40 CJ-4
Oil/Filter Service Intrevals	500HR—STD / 750HR—SYN

Polar Industrial Services Ltd.—2122 84 Ave, Edmonton AB, T6P 1K2 780-417-1190—www.polarind.ca—sales@polarind.ca





INDUSTRIAL DIESEL GENERATOR



Specifications

ELECTRICAL SYSTEM	
Volts (DC)	12V
Alternator Rating	55 Amp
Starter Rating	2.2KW
Min. Cold Cranking Amps	110 Amp
FUEL SYSTEM	
Recommended Fuel	#2 Diesel
Fuel Pump Type	Engine Driven
Injection Type	Mechanical Rotary Pump
Filter Type	Fuel/Water Separator
Fuel Tank Capacity	Optional 230L Tank
ALTERNATOR	
Manufacturer	Stamford
	Stamford S0L2-M41
Manufacturer	
Manufacturer Model	S0L2-M41
Manufacturer Model Alternator Type	SOL2-M41 4 Pole, Rotating Field
Manufacturer Model Alternator Type Exciter Type	SOL2-M41 4 Pole, Rotating Field Brushless, Self Exciting
Manufacturer Model Alternator Type Exciter Type Leads	SOL2-M41 4 Pole, Rotating Field Brushless, Self Exciting 4 Lead Designated
Manufacturer Model Alternator Type Exciter Type Leads Insulation System	SOL2-M41 4 Pole, Rotating Field Brushless, Self Exciting 4 Lead Designated
Manufacturer Model Alternator Type Exciter Type Leads Insulation System DIMENSIONS	SOL2-M41 4 Pole, Rotating Field Brushless, Self Exciting 4 Lead Designated Class H
Manufacturer Model Alternator Type Exciter Type Leads Insulation System DIMENSIONS Length	SOL2-M41 4 Pole, Rotating Field Brushless, Self Exciting 4 Lead Designated Class H 50"

Polar Industrial Services Ltd.—2122 84 Ave, Edmonton AB, T6P 1K2 780-417-1190—www.polarind.ca—sales@polarind.ca





INDUSTRIAL DIESEL GENERATOR



Specifications

ADDITIONAL FEATURES	
Control Panel	Dynagen TE410 Auto Start Controller
Block Heater	375W Lower Radiator Hose Heater
Battery Disconnect	Locking Battery Disconnect
Oil Drain	EZ Oil Drain Valve
Battery	Interstate MTP-24 with Battery Box
Serviceability	All Filters & Dipstick in Central Location

Shop tested under load before delivery, filled with high quality Mobil Lubricants

Warranty: 1 year/2000hrs

Engine Warranty: 3 year/2000hrs (6000hrs – Major Components)



Authorized Distributor













Polar Industrial Services Ltd.—2122 84 Ave, Edmonton AB, T6P 1K2 780-417-1190—www.polarind.ca—sales@polarind.ca